

HENKOVAC DOUBLE CHAMBERS:

EFFICIENT, HIGH CAPACITY AND BUILT TO LAST.

Our new range of double chambers are reliable, durable and offer flexibility in volume production. Our machines can be equipped with semi-automatic or automatic cover movement for an even more efficient production. The double chambers can also be equipped with an external pump.

“HEAVY DUTY, INDUSTRIAL PERFORMANCE,
INDUSTRIAL QUALITY”



DOUBLE CHAMBER D2



DOUBLE CHAMBER D6

SPECIFICATIONS D1, D3, D4 & D6

	SEAL LENGTH	MAX. PRODUCT HEIGHT	USEFUL CHAMBER SIZE (wxdxh)	OUTSIDE DIMENSION (wxdxh)	STANDARD VOLTAGE*	POWER CONSUMPTION	WEIGHT
STAINLESS STEEL COVER & FLAT WORKING SURFACE							
D1	4 x 620	230	620 x 520 x 230	1440 x 915 x 1205	400-3-50 Hz	4,4 kw	350 kg
D3	4 x 820	250	820 x 700 x 250	1800 x 1100 x 1230	400-3-50 Hz	6,2-9,7 kw	600 kg
D4	4 x 920	270	920 x 870 x 270	2000 x 1260 x 1245	400-3-50 Hz	6,2-9,7 kw	720 kg
ALUMINUM COVER & FLAT WORKING SURFACE							
D6	4 x 600	180	610x510x180	1345 x 720 x 1040	400-3-50 Hz	4,4 kw	240 kg

Dimensions in mm *Machines can be supplied with all worldwide voltages applicable

OPTIONS D1, D3, D4 & D6

	DIGITAL TIME CONTROL	SENSOR CONTROL	SEAL	SEAL CONFIGURATION	GAS	PUMP CAPACITY M3	CYCLE TIME
D1	10 programs	sensor/H ₂ O	double trenn 1-2 bi active	2x L&L	gas	63-100 m ³	20-40 sec
D3	10 programs	sensor/H ₂ O	double trenn 1-2 bi active	2x L&L	gas	160-300 m ³	20-35 sec
D4	10 programs	sensor/H ₂ O	double trenn 1-2 bi active	2x L&L	gas	160-300 m ³	25-40 sec
D6	1 or 10 programs	sensor/H ₂ O	double trenn 1-2 bi active	2x L&L	gas	40-63-100 m ³	20-40 sec

SEAL CONFIGURATIONS D1, D3, D4 & D6

