# Maximum flexibility

Modular Counter Cold



The Fri-Jado Modular Counter range delivers a speedy and easy shopping experience for both customers and operators, through:

- A well-lit, clean and inviting hot, cold and ambient food system to cover all fresh food categories
- An ergonomic design providing easy access
- Unobstructed visibility for the customer
- Easy to adapt to any format within new stores or retrofits
- Providing the opportunity for increased basket sales through meal deals

### Features MC Cold Curved

#### Top features

- Inline refrigerated display cabinet, full-serve or self-serve
- Can be combined with heated and ambient counters
- Available in 1000 and 750 mm width

#### Standard characteristics

- Product temperature maintained at between 5°C and 7°C
- Air circulation technology that holds temperature effectively
- Lighting on each shelf
- Thermo pane glass increased insulation
  - Double glass sliding doors, ideal for small areas with limited floor space
  - Stainless steel and powder-coated interior and exterior
- Ideal for sandwiches, rolls, dairy products, drinks and other meal solutions
- Point-of-sales promotion options in price strips



POS options



MC 100 Hot Curved



Three presentation levels

Various combinations possible





making food irresistible

|                   | MC 75 Cold FS | MC 75 Cold SS | MC 100 Cold FS | MC 100 Cold SS |
|-------------------|---------------|---------------|----------------|----------------|
| Width             | 750 mm        | 750 mm        | 1000 mm        | 1000 mm        |
| Depth             | 766 mm        | 766 mm        | 766 mm         | 766 mm         |
| Height            | 1516 mm       | 1516 mm       | 1516 mm        | 1516 mm        |
| Net weight        | 161 kg        | 163 kg        | 190 kg         | 185 kg         |
| Gross weight      | 188 kg        | 190 kg        | 224 kg         | 218 kg         |
| Temperature class | 3M2           | 3M2           | 3M2            | 3M2            |
| Voltage           | 1N~230V       | 1N~230V       | 1N~230V        | 1N~230V        |
| Frequency         | 50 Hz         | 50 Hz         | 50 Hz          | 50 Hz          |
| Power             | 1,3 kW        | 1,3 kW        | 1,3 kW         | 1,3 kW         |
| Refrigerant/GWP   | R134A / 1430  | R134A / 1430  | R134A / 1430   | R134A / 1430   |
|                   |               |               |                |                |


## MC 75 Cold Curved









## MC 100 Cold Curved







Specifications and technical data are subject to amendment without notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at www.frijado.com.



Fri-Jado B.V. P.O. Box 560 4870 AN Etten-Leur The Netherlands Phone +31 76 50 85 400 Fax +31 76 50 85 444 e-mail info@frijado.com www.frijado.com